

Determination of Benzene in Reformulated Gasoline

Using a Supelco® SLB®-IL111 Ionic Liquid GC Column

The amount of benzene in gasoline is a concern because it is a known human carcinogen, and exposure to it has been linked to detrimental health effects. The challenge with the analysis lies in the complex composition of gasoline, which consists of hundreds of different compounds. Reformulated gasoline also contains additives to produce more complete combustion and subsequent lower emissions of harmful compounds. These additives accomplish this by boosting the oxygen content, and are commonly referred to as "oxygenates". Ethanol is a commonly used oxygenate. Therefore, to measure benzene in reformulated gasoline, it must be resolved from the C5-C11 aliphatic portion, other aromatics, ethanol, plus any internal standards. This typically requires the use of a two-column switching procedure¹.

Figure 1 shows the analysis of a reformulated gasoline sample on the SLB-IL111. The extremely polar selectivity of this column resulted in the elution of benzene after the aliphatic portion, and also resolution of benzene and ethanol. Additionally, the phase stability of the SLB-IL111 column exhibits a stable baseline when subjected to a temperature ramp. Because this column can be used up to 270 °C, it also allows the timely elution of the heavy aromatic constituents in gasoline. These observations indicate that the SLB-IL111 may be an effective alternative to the two-column switching procedure currently required for the determination of benzene and other aromatics in reformulated gasoline.

Reference



1. ASTM® D3606, Benzene and Toluene in Unleaded Gasoline and Aviation Fuel.

Figure 1. Gasoline with 20% Ethanol and 4% Internals on the 60 m SLB-IL111

column: SLB-IL111, 60 m x 0.25 mm I.D., 0.20 µm (28928-U)
oven: 50 °C (3 min), 15 °C/min to 265 °C (5 min)
inj. temp.: 250 °C
detector: FID, 275 °C
carrier gas: helium, 30 cm/sec
injection: 0.5 µL, 200:1 split
liner: 4 mm I.D., split type, single taper wool packed FocusLiner™ design
sample: Premium unleaded gasoline, plus ethanol at 20% (v/v) and two internals each at 4% (v/v)

1. C5-C11 Hydrocarbons
2. Ethanol
3. Benzene
4. 2-Butanol (int. std.)
5. Methyl ethyl ketone (int. std.)
6. Toluene
7. Ethylbenzene
8. p-Xylene
9. m-Xylene
10. o-Xylene
11. 1,2,4-Trimethylbenzene
12. 1,2,3-Trimethylbenzene
13. 1,2,4,5-Tetramethylbenzene
14. Naphthalene
15. 2-Methylnaphthalene
16. 1-Methylnaphthalene

Great resolution of benzene from ethanol, internal standards, all aliphatic compounds, and all other aromatic components



Peak IDs (black = aliphatic; red = aromatic; blue = alcohol; green = int. std.)

SLB-IL111 Column Specifications

- **Application:** World's first commercial column to rate over 100 on our GC column polarity scale. Selectivity most orthogonal to non-polar and intermediate polar phases, resulting in very unique elution patterns. Maximum temperature of 270 °C is very impressive for such an extremely polar column. Great choice for separation of polarizable analytes (contain double and/or triple C-C bonds) from neutral analytes. Also a good GCxGC column choice. Launched in 2010.
- **USP Code:** None
- **Phase:** Non-bonded; 1,5-Di(2,3-dimethylimidazolium)pentane bis(trifluoromethylsulfonyl)imide
- **Temp. Limits:** 50 °C to 270 °C (isothermal or programmed)

Ordering Information

Description	Qty.	Cat. No.
SLB-IL111 Ionic Liquid Columns		
15 m x 0.10 mm I.D., 0.08 µm	1	28925-U
30 m x 0.25 mm I.D., 0.20 µm	1	28927-U
60 m x 0.25 mm I.D., 0.20 µm	1	28928-U
100 m x 0.25 mm I.D., 0.20 µm	1	29647-U



To view our ionic liquid GC column resources, visit sigma-aldrich.com/il-gc

Enabling Science to
Improve the Quality of Life

Order/Customer Service: sigma-aldrich.com/order
 Technical Service: sigma-aldrich.com/techservice
 Development/Custom Manufacturing Inquiries **SAFC*** safcglobal@sial.com
 Safety-related Information: sigma-aldrich.com/safetycenter

World Headquarters
3050 Spruce St.
St. Louis, MO 63103
(314) 771-5765
sigma-aldrich.com

©2013 Sigma-Aldrich Co. LLC. All rights reserved. SIGMA, SAFC, SIGMA-ALDRICH, ALDRICH and SUPELCO are trademarks of Sigma-Aldrich Co. LLC, registered in the US and other countries. FLUKA is a trademark of Sigma-Aldrich GmbH, registered in the US and other countries. LB is a registered trademark of Sigma-Aldrich Co. LLC. Solutions within is a trademark of Sigma-Aldrich Co. LLC. ASTM is a registered trademark of American Society for Testing and Materials. FocusLiner is a trademark of SGE Analytical Science Pty. Sigma-Aldrich, Sigma, Aldrich, Supelco, Fluka and SAFC brand products are sold by affiliated Sigma-Aldrich distributors. Purchaser must determine the suitability of the product(s) for their particular use. Additional terms and conditions may apply. Please see product information on the Sigma-Aldrich website at www.sigmaaldrich.com and/or on the reverse side of the invoice or packing slip.

PSX_DP
11901/T413209
1113